

Link do produktu: <https://bizongarage.pl/8-cyl-triple-d-dry-direct-port-3-stage-dry-6-solenoids-10lb-nitrous-express-nx-80020-10-p-38600.html>



8-Cyl Triple-D Dry Direct Port 3 Stage Dry 6 Solenoids 10LB Nitrous Express NX 80020-10

Cena brutto	16 959,99 zł
Cena netto	13 788,61 zł
Dostępność	Na zamówienie
Numer katalogowy	331562202
Kod producenta	USA-NX-80020-10

Opis produktu

8-Cyl Triple-D Dry Direct Port 3 Stage Dry 6 Solenoids 10LB This system includes the latest technology and the best components available. For you tech hungry junkies we will provide some details explaining what makes this nitrous system so great. The key to maximizing nitrous horsepower is to keep the nitrous in a dense liquid form until it is injected into the engine. Sharp bends in the nitrous flow path cause the nitrous flow to become turbulent which causes gaseous bubbles to form in the flowing nitrous. Dense liquid nitrous makes more power than gaseous nitrous Period! This NX nitrous system contains the key components that ensure you are getting maximum power per pound of nitrous used. Read on and we will explain. NX Lightning solenoids feature an improved flow path that allows nitrous to enter above the seat and exit out the bottom for flow unmatched by any other solenoid on the market. Lightning nitrous solenoids feature an integrated purge port which allows you to connect a purge valve directly to the body of the nitrous solenoid. Purging through the body of the solenoid eliminates the air pocket between the purge valve and the solenoid orifice. Lightning Series solenoids feature CNC aluminum bodies topped with Carbon Fiber cans for the ultimate in weight savings. Nitrous Express only uses the highest quality, made in the USA components in its solenoids. Do not be fooled by low price come-ons, the solenoids are the most important component of a nitrous system. This system includes: 8 of the NX Triple-D Nitrous Nozzles 6 NX Lightning series nitrous solenoids Anodized aluminum distribution blocks Billet aluminum shower head fittings 3/16 stainless hard lines Nickel plated fittings Jetting for 200-500HP per stage 8AN nitrous feed lines High flow 8AN Y-fitting Wide open throttle switch 40 Amp relays and relay harnesses Master arming switch Stainless bottle brackets and a 10lb nitrous bottle with the NX Lightning valve THE NITRO BOTTLE IS EMPTY! Instructions PDF