

Link do produktu: <https://bizongarage.pl/catch-can-kit-pcv-for-2022-subaru-brz-toyota-gr86-fluid-lock-radium-engineering-p-169456.html>



Catch Can Kit PCV for 2022+ Subaru BRZ / Toyota GR86 Fluid Lock Radium Engineering

Cena brutto	1 148,99 zł
Cena netto	934,14 zł
Numer katalogowy	USA-RAD-20-0911-FL

Opis produktu

COMPATIBILITY 2022+ Toyota GR86 2022+ Subaru BRZ **OVERVIEW** An oil catch can is essential to protect the engine from elevated levels of crankcase blow-by accumulated from aggressive driving. Excess oil-saturated air circulating back into the air intake stream can lead to degraded performance. Radium Engineering catch cans feature large 10AN ORB ports, a 4AN ORB drain port, 2-step oil separation baffling, and an O-ring sealed dipstick. **FEATURES**-Less oil consumption effectively raises octane-Cleaner air increases engine performance -Prevents sludge buildup in the intake-Lowers hydrocarbon emissions -Capacity: 7 fluid ounces -Height (without fittings): 5 inches-Outside Diameter: 2.45 inches **PLATFORM SPECIFIC** The catch cans are strategically located for compatibility with Right Hand Drive (RHD) and Left Hand Drive (LHD) variations. Minor brake line clearancing is necessary on RHD installations. For mounting, the kits use factory bosses and holes on the chassis. No cutting, drilling or permanent modification to the vehicle are required. The two oil catch can kits are completely independent of each other and are sold individually or together. They do NOT vent to atmosphere (VTA), thus are emissions and track legal. Closed loop systems route clean filtered air back in through the engine to be burned and to promote negative crankcase pressure for optimal performance. Furthermore, closed systems prevent unwanted oil vapors into the cabin. **20-0911-FL CATCH CAN KIT, PCV, 2022+ BRZ/GR86, FLUID LOCK** The 20-0911-FL PCV kit mounts on the RH side of the engine bay. This catch can runs inline with the 5/8" PCV (positive crankcase ventilation) valve. When the intake manifold pressure is close to or greater than atmospheric pressure, the PCV "check" valve closes and, thus, this hose experiences no flow. Conversely, the PCV hose will experience "metered" vacuum when the engine is idling, steady state cruising, and decelerating. This would normally draw unwanted crankcase vapor, unspent fuel, and oil sludge into the intake manifold immediately after a high load run. **20-0913-FL DUAL CATCH CAN KIT, 2022+ BRZ/GR86, FLUID LOCK** For the ultimate in engine protection, Radium Engineering recommends the 20-0913-FL Dual Catch Can Kit. This kit utilizes both the CCV and PCV catch can kits. **Instruction PDF**