

Link do produktu: <https://bizongarage.pl/fcst-x-2-for-external-pumps-radium-engineering-p-4168.html>

## FCST-X 2 for External Pumps Radium Engineering



Cena brutto	<b>4 229,00 zł</b>
Cena netto	<b>3 438,21 zł</b>
Dostępność	<b>Na zamówienie</b>
Numer katalogowy	<b>331498328</b>
Kod producenta	<b>USA-RAD-20-1995-00</b>

### Opis produktu

**LEGACY FCST FEATURE**The features listed below carry over from previous fuel cell surge tanks.-Merged single 10AN ORB female threaded outlet. All pumps use check valves that prevent back-flow.-One-way fill valves (355LPH each) allows fuel in, but not out, keeping the surge tank full.-Multiple fuel pump options including gerotor, turbine, and brushless DC motor pumps.-Hermetically sealed high-current stainless steel electrical studs capable of handling all pumps.-Simplified servicing eliminates sealing washers and fuel cell retaining brackets.-Full CNC aluminum construction with anodized surfacing for superior corrosion resistance.-Fuel compatibility: leaded and unleaded gasoline, methanol, ethanol, E85, etc.-Optional fuel surge tank level switch and diagnostic LED failsafe port.-Rollover vent valve protection

**NEW FEATURES**In addition to all previous FCST features, the new FCST-X rendition is packed with innovations.-Fast lift and surge pump access (9 bolts total)-Integrated lift handle for fuel pump servicing-Lightweight surge tank increased from 2.2L to 2.6L-Compatible with up to 4 brushless fuel pumps-Up to 4 Bosch BR540 fuel pumps (DW400) -Up to 3 Ti Automotive E5LM brushless pumps-Up to 4 brushless Bosch pumps (DW440)-Compatible with 16AN inlet mechanical pumps-Easily swappable pump modules (sold separately)-Compatible with shrouded level sensors-Designed with less potential leak points-Improved fluid control for quick filling-Optimized internal fluid management-Enhanced roll over protection-Anti-rotation electrical terminals

**WHAT'S IN THE BOX?**The following comes standard with every FCST-X variation-Anodized aluminum 6x10 plate-Anodized aluminum surge tank pump hat-Anodized aluminum lift pump hat-Anodized aluminum service handle-Anodized aluminum level sensor plate-Anodized aluminum surge pump bracket-Stainless lift pump mounts (shallow and deep)-Lift pump and surge pump fuel filters-Anodized aluminum 8AN roll over vent valve-FKM refueling rollover protection seal-FKM 6x10 24-hole sealing gasket-8AN ORB to 6AN male return fitting-10AN ORB to 8AN male pump out fitting-2AN ORB fuel level switch plug-FKM 1-way fill valves (x3)-Anodized aluminum acorn nuts-Electrical wire ring terminals

20-1990-00This FCST-X does not include fuel pumps. It can hold up to 3 surge tank pumps and 1 lift pump of the following. PUMP COMPATIBILITY- Walbro GSS342- AEM 50-1200- \*Deatschwerks DW440\*Use the electrical connector provided with the pumps. 20-1990-02This FCST-X is preassembled with 1 Walbro GSS342 lift pump and 2 Walbro GSS342 surge tank pumps. 20-1990-03This FCST-X is preassembled with 1 Walbro GSS342 lift pump and 3 Walbro GSS342 surge tank pumps. 20-1991-00This FCST-X does not include fuel pumps. It can hold up to 3 surge tank pumps and 1 lift pump of the following.NOTE: If using the optional fuel level switch inside the surge tank, only 2 surge tank pumps and 1 lift pump can be used. PUMP COMPATIBILITY- \*\*Bosch BR540- \*Deatschwerks DW400\*Use the electrical connector provided with the pumps. For the lift pump, use the filter sock provided with the pump.\*\*Because this pump does not include a built-in check valve, multiple surge pumps must be ran together (not staged). 20-1992-00This FCST-X does not include fuel pumps. It can hold up to 3 surge tank pumps and 1 lift pump of the following. PUMP COMPATIBILITY- Walbro F90000267- Walbro F90000274- Walbro F90000285- \*Walbro F90000295\*Because this pump does not include a built-in check valve, multiple surge pumps must be ran together (not staged). 20-1992-01This FCST-X is preassembled with 1 Walbro F90000274 lift pump and 1 Walbro F90000274 surge tank pump. 20-1992-02This FCST-X is preassembled with 1 Walbro F90000274 lift pump and 2 Walbro F90000274 surge tank pumps. 20-1992-03This FCST-X is preassembled with 1 Walbro F90000274 lift pump and 3 Walbro F90000274 surge tank pumps. 20-1993-00This FCST-X does not include fuel pumps. It can hold up to 2 surge tank pumps and 1 lift pump of the following. SURGE PUMP COMPATIBILITY- \*Ti Automotive E5LM (check valves included)LIFT PUMP COMPATIBILITY- \*Ti Automotive E5LM- \*\*Walbro F90000267- \*\*Walbro F90000274- \*\*Walbro F90000285- \*\*Walbro F90000295\*This pump requires a brushless controller. These typically come standard when purchasing the pump. See Ti Automotive BKS1001.\*\*For these pumps, it is recommended to use the Radium Engineering 14-0143 filter sock. 20-1995-00There are two 80u (micron) filters included for two 10AN (5/8") pickups. If using the provided 16AN (1") pickup, an external filter will need to be purchased.The surge tank can be configured to use any combination of the following: SURGE TANK COMPATIBILITY- (1x) 10AN pickup (shown below) for an inline external pump or mechanical pump. - \*(2x) 10AN pickups for an inline external pump and/or mechanical pump.- (1x) 16AN pickup for an inline external pump or

---

mechanical pump.- \*(1x) 16AN pickup and (1x) 10AN pickup (shown below) for an inline external pump and/or mechanical pump. \*An electric pump can be used to prime a mechanical pump (for faster engine starting) when running 2 of the pickups.This FCST-X does not include a fuel pump for the lift pump. It is compatible with the following.LIFT PUMP COMPATIBILITY- Walbro F90000267- Walbro F90000274- Walbro F90000285- Walbro F90000295 Instruction PDF