

Link do produktu: <https://bizongarage.pl/fuel-hanger-fits-walbro-f9000267274285-or-brushless-pump-radium-engineering-for-acura-integra-honda-civic-cr-x-p-46538.html>



Fuel Hanger fits Walbro F9000267/274/285 or Brushless Pump Radium Engineering for Acura Integra Honda Civic CR-X

Cena brutto	999,99 zł
Cena netto	813,00 zł
Numer katalogowy	USA-RAD-20-1792

Opis produktu

FUEL PUMP HANGER COMPATIBILITY 90-93 Acura Integra (All models/trims/RHD/LHD) 88-91 Honda Civic (All models/trims/RHD/LHD) 88-91 Honda CR-X (All models/trims/RHD/LHD) OVERVIEW This Radium Engineering fuel hanger replaces the stock fuel pump assembly. No cutting or modifying of the vehicle's sheet metal or fuel tank is required for installation. The fuel pump is positioned in the factory collector bowl for fuel starvation protection. PORT FITTINGS The fuel pump outlet is tapped for 8AN ORB (3/4"-16) female threads on the top plate. The preinstalled -6AN male fitting permits an aftermarket feed line and/or connects to the plumbing kit. The return inlet is tapped for 6AN ORB (9/16"-18) female threads on the top plate. The provided -6AN male fitting permits an aftermarket return line and/or connects to the plumbing kit. All fittings are machined low enough to clear the trunk sheet metal. FUEL PUMPS Part numbers 20-1790 and 20-1792 are configured to be used with 1 aftermarket fuel pump. Notes: If 2 aftermarket pumps are required, the supplementary "dual pump add-on" (20-1796 or 20-1797 listed below) is also required. If installing a brushless pump, the "dual pump add-on" CANNOT be used due to the extra brushless controller wires. Choosing the best fuel pump(s) is based on the expected engine power output, fuel type (gasoline, E85, etc.), and fuel pressure. P/N: 20-1790 **AEM 50-1000 **AEM 50-1200 **AEM 50-1220 **AEM 50-1230 **AEM 50-1235 *Walbro GSS342 P/N: 20-1792 *Walbro F90000267 *Walbro F90000274 *Walbro F90000285 *+Walbro F90000295 *+Ti Automotive E5LM (brushless) **Protec 11928 (brushless) **Fuelab 49614 (brushless) **Deatschwerks DW440 (brushless) **Deatschwerks DW810 (brushless) *Sock filters are included in this kit for these pumps.**Sock filters are included by the fuel pump manufacture.+These pumps do NOT feature a check valve. ELECTRICAL The custom designed ant-rotation stainless steel electrical studs easily handle the high current demand that compact multi-pin bulkhead connectors lack. These serviceable connections are hermetically sealed and impervious to all standard and exotic fuels. Non-conductive anodized aluminum acorn nuts are provided to prevent any accidental short circuiting. Furthermore, the in-tank wiring is insulated with high quality chemically resistant ETFE. Notes Single Walbro GSS342 (255LPH) fuel pump installations can re-use the OEM fuel pump wiring. It is recommended to upgrade OEM wiring to ensure the pumps are receiving full power and operating at their full potential. FEATURES Drop-In Installation Anodized Aluminum Construction Merged 8AN ORB Female Pump-Out Port Fittings for Aftermarket Fuel Lines Capable of 2 Pumps with Add-On Compatible with Various Pumps Included Fuel Pump Filter Sock High Current Electrical Hardware Stainless Steel Hardware and Clamps Gasoline, Methanol, and E85 Compliant Anti-rotation Electrical Terminals Instruction PDF