

Link do produktu: <https://bizongarage.pl/fuel-pulse-damper-fpd-xr-8an-orb-direct-mount-kits-radium-engineering-p-35702.html>



## Fuel Pulse Damper FPD-XR 8AN ORB Direct Mount Kits Radium Engineering

Cena brutto	<b>508,16 zł</b>
Cena netto	<b>413,14 zł</b>
Dostępność	<b>Na zamówienie</b>
Numer katalogowy	<b>331171326</b>
Kod producenta	<b>USA-RAD-20-0177</b>

### Opis produktu

The opening and closing of fuel injectors creates pressure pulses in the fuel rail which can lead to unstable fuel pressure. In order to achieve a safe and consistent rail pressure, a fuel pulse damper (FPD) is often necessary. The FPD's internal diaphragm will absorb oscillating pulses and stabilize fuel pressure. This correction can be measured throughout the RPM range and can often help idle surge, especially with high flow injectors. Furthermore, a fuel pulse damper can help solve erratic lean air/fuel ratio spikes, commonly experienced as "stumbling", that are difficult to tune out.

For more in-depth information on the function of fuel pulse dampers, read the Radium blog.

**NOT RECOMMENDED FOR THE LOW PRESSURE SIDE OF MECHANICAL FUEL PUMPS**

What makes Radium FPDs unique?

Along with having the flexibility of using common fittings, Radium Engineering FPD's use a vacuum/boost reference port which allows for proper fuel pulse damper performance even at elevated fuel pressures. This becomes essential for boosted systems that use a 1:1 rising rate fuel pressure regulator.

What is the difference between FPD-R and FPD-XR?

The FPD-R (green top) is slightly shorter than the FPD-XR (black top) allowing it to be used in space-constrained applications.

**WHICH DAMPER DO I CHOOSE?**

The FPD-R (Fuel Pulse Damper-Range) and FPD-XR (Fuel Pulse Damper-Extra Range) both have unique base "static" fuel pressure requirements:

FPD-R base pressure requirement = 40 - 70psi (static)

FPD-XR base pressure requirement = 40 - 105psi (static)

Base pressure is the fuel pressure measured when the fuel pump is running WITHOUT a vacuum line connected to the regulator.

**IMPORTANT:** The ranges above are base static fuel pressures only. Any dynamic fuel pressure created by a rising-rate FPR outside of this range is acceptable, but only when the base "static" fuel pressure is set within these ranges and the vacuum/boost reference line is connected.

---

Example 1:

Vehicle: Mitsubishi EVO

OEM Base Static Fuel Pressure: 43.5psi

Boost Pressure: 30psi

Rising Rate Pressure Regulator? Yes

Can I use a FPD-R? Yes. Even though fuel pressure is 73.5psi at full boost, the FPD-R will work because the base static pressure was set within the 40-70psi requirement. However, the vacuum/boost reference line must be installed.

Can I use a FPD-XR? Yes. Also, the vacuum/boost reference line does not need to be installed since maximum fuel pressure does not exceed 105psi.

Example 2:

Vehicle: BMW E46 M3

OEM Base Static Fuel Pressure: 72.5psi

Boost Pressure: 20psi

Rising Rate Pressure Regulator? Yes

Can I use a FPD-R? No. Base static fuel pressure exceeds the 40-70psi requirement.

Can I use a FPD-XR? Yes. Also, the vacuum/boost reference line does not need to be installed since maximum fuel pressure does not exceed 105psi.

Included

-Anodized and laser engraved aluminum top, R=range or XR=extra range

-Anodized aluminum body with male threads, 8AN ORB or 3/8" NPT

-Stainless steel hardware

-Rubber vacuum hose, 4mm ID

-Vacuum hose Y-fitting

[Instruction PDF](#)