

Link do produktu: <https://bizongarage.pl/fuel-pump-hanger-radium-engineering-for-bmw-e46-p-46534.html>

## Fuel Pump Hanger Radium Engineering for BMW E46



Cena brutto	<b>2 499,99 zł</b>
Cena netto	<b>2 032,51 zł</b>
Numer katalogowy	<b>USA-RAD-20-1180</b>

### Opis produktu

20-1180 FUEL PUMP HANGER COMPATIBILITY 99-05 BMW E46 316i 98-06 BMW E46 318i 98-06 BMW E46 320i 98-00 BMW E46 323i 01-06 BMW E46 325i 98-00 BMW E46 328i 00-06 BMW E46 330i 03-06 BMW E46 330i ZHP 00-06 BMW E46 M3 03-04 BMW E46 M3 CSL OVERVIEW This Radium Engineering fuel hanger replaces both RH and LH fuel hat assemblies. It is compatible with 1 or 2 aftermarket fuel pumps. The kit reuses both passive side and active side fuel level sensors. It is also keeps a true saddle tank crossover system using new improved components. No cutting or modifying of the vehicle is required for installation. FITTINGS The merged fuel pump outlet is tapped for 10AN ORB (7/8"-14) female threads on the top plate. However, an SAE quick connector barb is provided to connect to the OEM feed line. The fuel return inlet is tapped for 10AN ORB (7/8"-14) female threads on the top plate. However, an 8.5mm barbed adapter is provided to connect to the OEM return line. All fittings are machined low enough to clear the surrounding area. COMPATIBLE FUEL PUMPS The 20-1180 is configured to be used with 1 or 2 aftermarket fuel pumps. These can be 2-wire brushed fuel pumps or 3-4 wire brushless fuel pumps. Choosing the best fuel pump is based on the expected engine power output, fuel type (gasoline, E85, etc.), and fuel pressure. AEM 50-1000 AEM 50-1200 Walbro GSS342 Walbro F90000267 Walbro F90000274 Walbro F90000285 \*Walbro F90000295 \*Ti Automotive E5LM Protec 11928 / Fuelab 49614 Deatschwerks DW440 Deatschwerks DW810 \*These pumps do not feature an integrated check valve. If a check valve is necessary, purchase 20-1534 (separately) to replace the fitting(s) under the fuel hat. ELECTRICAL The custom designed stainless steel electrical studs easily handle the high current demand that compact multi-pin bulkhead connectors lack. They have an anti-rotation feature that prevents the terminals from spinning. These serviceable connections are hermetically sealed and impervious to all standard and exotic fuels. Non-conductive anodized aluminum acorn nuts are provided to prevent any accidental short circuiting. Furthermore, the in-tank wiring is insulated with high quality chemically resistant ETFE. NOTES Single pump installations can re-use the OEM fuel pump wiring. It is recommended to upgrade OEM wiring to ensure the single pump is receiving full power and operating at maximum potential. If using a second pump, a new dedicated relay and fuse pump MUST be used. FEATURES Drop-In Installation Aluminum and Stainless Construction PRV Venturi Jet Pump Siphon Merged 10AN ORB Female Pump-Out Port Compatible with Various Pumps Brushless Fuel Pump Capable Fuel Pump Filter Socks Included Capable of Running 1 or 2 Fuel Pumps Anti-Rotation Electrical Terminals High Current Electrical Hardware Gas, Methanol, and E85 Compliant Instruction PDF