

Link do produktu: <https://bizongarage.pl/fuel-rail-plumbing-kit-for-nissan-r35-gt-r-vr38dett-radium-engineering-p-4107.html>



## Fuel Rail Plumbing Kit for Nissan R35 GT-R VR38DETT Radium Engineering

Cena brutto	<b>3 239,00 zł</b>
Cena netto	<b>2 633,33 zł</b>
Dostępność	<b>Na zamówienie</b>
Numer katalogowy	<b>331498119</b>
Kod producenta	<b>USA-RAD-20-0956-PK</b>

### Opis produktu

#### PORTS AND FITTINGS

The fuel rail ports are tapped for 8AN ORB.

8AN ORB Adapter Fittings  
8AN ORB Fuel Pulse Dampers  
Fuel Pressure Gauge Adapters

#### PLUMBING KIT

##### 20-0956-PK Fuel Rail Plumbing, Nissan R35 GT-R

When used with the 20-0556-02 fuel rails, this kit permits a bolt-on, plug and play affair. A stainless steel mount is provided for the Radium FPR. Low profile 90 degree SAE adapters with PTFE fuel hoses connect the OEM hard fuel lines to the FPR. PTFE fuel lines run from the FPR to the rear fuel rail ports. Two Radium fuel pulse dampers and a pressure gauge are included and all necessary adapter fittings.

RA-series regulators feature the first tool-less pressure adjustment. A jam nut and set screw are no longer required. With a simple turn of the knob, pressure will be increased or decreased. To aid in adjusting pressure, there are incremental detents that provide haptic feedback to the user. Every detent permits 1psi (+/-0.5psi) of adjustment depending on current fuel pressure.

RA-series regulators feature a 360 degree swiveling vacuum reference port that is double O-ring sealed. This is the first in the industry. It permits the installer to quickly point the vacuum fitting in any direction with no tools required.

There are 4 interchangeable 10-32 threaded vacuum port fittings provided to cover all scenarios.

1. Barbed Fitting: A black zinc-plated 3/16" (5mm) barb machined from high strength steel that is compatible with the following vacuum hoses: 5/32" (4mm), 3/16" (5mm), and 7/32" (6mm).
2. 3AN Male Fitting: A black zinc-plated adapter machined from high strength steel that is compatible with 3AN hose ends.
3. Push-To-Connect: A nickel-plated brass fitting with Buna-N O-rings that is compatible with hard plastic 1/4" OD tubing.
4. Vacuum Plug: A black oxide stainless steel screw that is used to maintain a constant (non dynamic) fuel pressure.

[Instruction PDF](#)