

Link do produktu: <https://bizongarage.pl/greddy-injector-kit-for-nissan-sr20det-s14s15-oem-834-cc-p-183678.html>

## GReddy Injector Kit for Nissan SR20DET (S14/S15, OEM) - 834 CC



Cena brutto	<b>4 432,56 zł</b>
Cena netto	<b>3 603,71 zł</b>
Numer katalogowy	<b>13923311</b>

### Opis produktu

GReddy Injector Kit To suit Nissan SR20DET Black Top (S14 & S15) Flow rate(s) : 695 cc/min, 834 cc/min, 931 cc/min Type : top feed Direct OEM replacement Flawless quality and reliability GReddy part number(s) : 13923310, 13923311, 13923312, 13923313, 13923314, 13923315 GReddy Injector Kit for Nissan SR20DET (S14/S15) Specifications This GReddy kit, specially designed for the Nissan S14 and S15 SR20DET engine, includes a fuel rail and a set of 695 cc, 834 cc or 931 cc injectors (as required) with connectors, terminals and sleeves to significantly improve the fuel supply to the turbocharged Nissan 4-cylinder. Developed to be 100% "plug and play", this kit combines top quality and reliability and can be installed in place of the OEM components, with no modifications required. Please note that this kit is available in two variants: compatible with the stock intake manifold (surge tank) or compatible with the GReddy intake manifold (surge tank). Technical Data P/N 13923310 / 13923313 Flow rate (cc/min) : 695 (3 bar) System : top feed Spray pattern : conical (9 holes) Connector : Jetronic (square) Resistance : 12 Ω P/N 13923311 / 13923314 Flow rate (cc/min) : 834 (3 bar) System : top feed Spray pattern : conical (7 holes) Connector : Jetronic (square) Resistance : 12 Ω P/N 13923312 / 13923315 Flow rate (cc/min) : 931 (3 bar) System : top feed Spray pattern : conical (7 holes) Connector : Jetronic (square) Resistance : 12 Ω Kit Details for Stock Surge Tank (See Diagram) 1) Fuel delivery tube x12 AN6/M20 adapter union x33) M20 plug union x14) O-ring (P18) x45) Spacer (37 mm) x16) Spacer (20 mm) x27) Cap bolt M8 P1.25 (L=60) x18) Cap bolt M8 P1.25 (L=40) x29) M8 spring washer x310) M8 flat washer x311) O-ring (S11.2) x412) I/J conversion adapter (out side) x413) O-ring (P21) x414) IAA unit adapter x115) ø15-1/4PT hose union x116) Cap bolt M6 P1.0 (L=55) x317) M6 spring washer x318) M6 flat washer x319) IAA unit gasket x220) Hose joint ø15 x121) Hose band #8 x222) Acrylic hose ø15 500 mm x123) Injector assy x424) Connector set x4