

Link do produktu: <https://bizongarage.pl/kute-korbowody-ze-srubami-l19-heavy-duty-zrp-honda-k24-152mm-x-22mm-p-7519.html>



Kute korbowody ze śrubami L19 Heavy Duty ZRP Honda K24 152mm x 22mm

| | |
|------------------|------------------------------|
| Cena brutto | 3 149,99 zł |
| Cena netto | 2 560,97 zł |
| Dostępność | Na zamówienie |
| Numer katalogowy | 331574109 |
| Kod producenta | R-HON-EN24T-017-I-L19 |

Opis produktu

The I-Beam "Heavy Duty" series Connecting rods for Honda K24 aimed for the High Hp applications. Built from the finest raw materials 4340-EN24T high tensile steel with a specially optimized shape for high performance and extreme durability. The "straight cut" pin end increases durability, so they can only be used in conjunction with aftermarket pistons. The bushings are made from AMPCO 18 material, for excellent resistance to wear and fatigue and have radial groove acting as an oil reservoir. They are shot peened to relieve stress from the material and multi-stage heat treated to increase rigidity. The tight tolerances in the production process, ensure a perfect fitment while optimizing the oil clearances. Bend and twist is tightly controlled. Each rod includes 3/8 ARP 2000 cap fasteners that are rated at 220,000psi, optional ARP L19 material 260.00psi available as an upgrade and the whole kit is supplied with ARP moly and full fitting instructions.

Additional machining processes

- Dowel sleeves for perfect fit and accurate re-assembling
- Lipped Cap Relief for improved big-end integrity at extreme application
- Grooves in Thrust Face for weight reduction

Technical Features of ZRP Connecting Rods

- Two-Piece forging for great strength
- I-Beam Shape for extra rigidity
- Shot Peening for improved fatigue life
- Magnaflux Inspection guarantees that the consistency of the forged material meets our high-quality standard
- Double ribbed caps for added support
- Multi Stage Heat Treatment for maximum strength, dimensional stability, and fatigue life.
- CNC machining for superior tolerances, precise as much as 0.0002"
- Center to center is maintained under .001" tolerance
- Finite Element Analysis (FEA) Computer generated stress analysis of con rods
- Optimal balancing for weight matched sets of ± 1 gram

Additional information

| | |
|-------------|-------------------------------------|
| Engine Nr | K24 Series |
| Application | 2.4L K24 |
| Notes | Recommended usage: High RPM Engines |
| Bolt Size | 3/8" |
| Shape | I-Beam |
| Length (CC) | 152.00 |
| Pin Size | 22.00 |
| Big Bore | 51.00 |
| B.E Width | 19.81 |

| | |
|----------------|------------|
| Weight Gr. | 534 |
| Set of | 4 |
| Fastener Grade | ARP2000 |
| Series | Heavy Duty |
| Weight | 534 |