

Link do produktu: <https://bizongarage.pl/kute-korbowody-ze-śrubami-l19-zrp-vw-audi-14l-tfsi-ea111-non-rifle-drilled-144mm-x-19mm-p-7523.html>



Kute korbowody ze śrubami L19 ZRP VW / Audi 1.4L TFSI EA111 (Non-Rifle Drilled) 144mm x 19mm

Cena brutto	2 879,99 zł
Cena netto	2 341,46 zł
Dostępność	Na zamówienie
Numer katalogowy	331574088
Kod producenta	R-VW-004-H-L19

Opis produktu

Audi / VW 1.4L TSI & TFSI Connecting rods are H-Beam shaped and manufactured from 4340 high tensile steel. The bushings are made from AMPCO 18 material, for excellent resistance to wear and fatigue and have radial groove acting as an oil reservoir. They also have "Ribbed pin end" that minimizes pin end distortion under heavy inertial loads while saving excess weight. They are shot peened to relieve stress from the material and multi-stage heat treated to increase rigidity. The tight tolerances in the production process, ensure a perfect fitment while optimizing the oil clearances. Bend and twist is tightly controlled. They are designed for high performance and extreme durability.

Each rod includes ARP 2000 cap fasteners that are rated at 220,000 psi , optional ARP 625 material available as an upgrade and the whole kit is supplied with ARP moly and full fitting instructions.

Additional machining processes

- Dowel sleeves for perfect fit and accurate re-assembling
- Lipped Cap Relief for improved big-end integrity at extreme application
- Grooves in Thrust Face for weight reduction

Technical Features of ZRP Connecting Rods

- Two-Piece forging for great strength
- Shot Peening for improved fatigue life
- Magnaflux Inspection guarantees that the consistency of the forged material meets our high-quality standard
- Double ribbed caps for added support
- Multi Stage Heat Treatment for maximum strength, dimensional stability, and fatigue life.
- CNC machining for superior tolerances, precise as much as 0.0002"
- Center to center is maintained under .001" tolerance
- Finite Element Analysis (FEA) Computer generated stress analysis of con rods
- Optimal balancing for weight matched sets of ± 1 gram

Additional information

Application	1.4L TFSI (2012-Pre)
Engine Nr	CAVD , CAXA , CAVA , BLG , CAX , CAV , CVA
Notes	Non-Rifle Drilled Rods
Bolt Size	5/16"
Shape	H-Beam
Length (CC)	144.00
Pin Size	19.00
Big Bore	50.60
B.E Width	23.00
Weight Gr.	467

Set of
Fastener Grade
Series
Weight

4
ARP2000
Standard Series
467