

Link do produktu: <https://bizongarage.pl/nuke-performance-alucell-fuel-cell-20l-with-low-profile-cfc-unit-standard-p-4568.html>



Nuke Performance AluCell Fuel Cell 20L with Low Profile CFC Unit (Standard)

Cena brutto	5 898,99 zł
Cena netto	4 795,93 zł
Dostępność	Na zamówienie
Numer katalogowy	331561532
Kod producenta	NP-150-07-021

Opis produktu

AluCell Aluminum Fuel Cells, a lightweight and affordable fuel cell combined with the Nuke Performance drop-in surge tank, the CFC Unit. This product offers an affordable solution for those who do not require FIA approval for professional racing, but still want all the benefits from the Nuke Performance CFC Unit. The drop-in fuel pump hanger with integrated surge tank provides this functionality featuring: 20 / 40 / 45WC / 60 / 80 liter aluminum fuel cell Integrated 2.0 liter Fuel Surge Tank function Safe for all types of fuels, including E85 Integrated brackets for easy and secure mounting Fits single or dual high-pressure fuel pumps A single oversized AN-10 ORB outlet, for maximal flow NEW : Available in a new 45 liter Well Cell version Low-profile fuel filler cap with integrated roll-over valve The Nuke Performance AluCell fuel cells are suitable for carburetor-based fuel systems and with the integrated CFC Unit from Nuke Performance. They eliminate the need for an external surge tank which would otherwise be needed when running a fuel cell, making it a perfect alternative for fuel-injected systems. The AluCells are made of the highest quality aluminum for use with all types of fuels and are approved for petrol, methanol, and ethanol. AluCell Specifications 40 liter AluCell Part # 150-07-041 Length 555mm (21.85") Depth 377mm (14.84") Height 251mm (9.88") Weight 9050g (19.95lb), incl. CFC Unit Fuel capacity 40-liter (10.56 gallons) For motorsports use YES Homologation NO EAN 7340209500356 AluCell Fuel Cell Kit includes: 1 x AluCell Aluminum fuel cell 20-liter / 40-liter / 60-liter / 80-liter 1 x Nuke Performance CFC Unit - low profile version 2 x 1/4" BSPP to Male barb 8mm hose fittings 1 x 1/4" BSPP plug, when using only one high-pressure fuel pump 2 x 39mm inserts for high-pressure fuel pump bracket 1 x Viton gasket for 24 bolt pattern fuel cells (safe for alcoholic fuels) 1 x Low profile filler cap (remote fill neck available as accessory) 1 x Dual billet fuel pump bracket and adjustable pickup pump mount 1 x AN-8 (3/4 UNF) to AN-6 Male vent safety valve 1 x FLS spacer, used for fuel level senders with a not symmetrical bolt pattern 24 x 1/4-28 UNF x 1 bolts with nylon washers