

Link do produktu: <https://bizongarage.pl/ts-2-performance-turbocharger-water-cooled-6262-v-band-082ar-internally-wastegated-p-52802.html>



TS-2 Performance Turbocharger (Water Cooled) 6262 V-Band 0.82AR Internally Wastegated

Cena brutto	11 939,99 zł
Cena netto	9 707,31 zł
Numer katalogowy	TS-2-6262B-VB082I

Opis produktu

Smaller, Lighter and Faster - Turbosmart's turbocharger series has been developed to leverage modern materials, design and manufacturing techniques to create a turbocharger range that meets the demands of both motorsport, and performance enthusiasts alike. Every Turbosmart turbocharger comes standard with everything you need for installation, weld flanges, V-band clamps, gaskets, oil feed and drain fittings as well as water feed and return fittings are included. The TS-2 series are water and oil cooled turbochargers with lightweight investment cast turbine housings, a proprietary bearing and main shaft combination which will provide transient response you never knew possible with the type of performance, quality, reliability and support you've come to know Turbosmart for. The ultra-low rotating mass of our unique bearing and shaft assembly is matched to aggressive compressor aerodynamics to ensure high levels of performance at lower shaft speeds which is mated with a unique turbine wheel to ensure power at high loads and flow is maintained. The TS-2 turbocharger series has taken an engine end-to-end approach aiming to achieve power through reduced back pressure and high performance turbines - While being smaller, lighter and faster in response than other solutions on the market. Features Unparalleled transient response Aggressive aerodynamics with 7+7 2618 Aluminium splitter wheels Lightweight 310s stainless steel investment cast turbine housings Lightweight, Aluminium compressor covers CFD driven designed housings for optimal A/R's and flow 713C Inconel turbine wheel for extreme EGT's VSR speed balanced Proprietary dual ceramic bearing system Integrated Iron backplate on center housing Specifications Compressor Inlet: 4" / 101.6mm Compressor Inducer: 62mm Turbine Inlet: V-Band (2.25") Turbine Exducer: 62mm Turbine AR: 0.82 Turbine Outlet: V-Band (3.00") Weight: 6.06kg / 13.3lbs Horsepower Rating: 760-880HP