

Link do produktu: <https://bizongarage.pl/turbosprezarka-pulsar-psr-7382gr-1550hp-128-t4-divided-wlot-3-v-band-wylot-kozyska-kulkowe-p-53502.html>



## Turbosprężarka Pulsar PSR 7382GR 1550HP 1.28 T4 Divided wlot 3" V-Band wylot łożyska kulkowe

|                  |                    |
|------------------|--------------------|
| Cena brutto      | <b>6 099,99 zł</b> |
| Cena netto       | <b>4 959,34 zł</b> |
| Numer katalogowy | <b>102145248</b>   |

### Opis produktu

PSR 7382GR Dual Ball Bearing Turbocharger HP Rating 1550 for Class Legal Race Dual ceramic ball bearing system provides optimal turbo response & better durability by reducing the shaft-motion 7+7 Blade GR compressor wheel will get more air flow 9 Blade G-Aero Inconel 713c turbine wheel Anti-Surge ported-shroud compressor inlet, cover integrated with the speed sensor and pressure ports Water and oil fittings included with the super core 8 Options in Turbine Housing HP rated at 1500HP at flywheel Installation Hardware: 3" flange kit for Comp. Outlet, T4 Gasket/3" flange kit for Turb. Inlet, 3.5"/4" flange kit for Turb. Outlet and oil Drain Fitting kit are included by default Oil Feed Fitting(-4AN 1.65mm (0.065") Orifice) included Compressor Housing: Standard Turbine Housing: T4 Divided 1.28A/R A stainless steel gasket T4 open included for turbine housing inlet; A flange kit included for turbine housing outlet fits 3.5" OD tubing, slip on and weld. Compressor Wheel: 73.9\*102mm, 7+7 Blade Turbine Wheel: 89\*81.6mm Compressor Inlet: 5" Hose Compressor Outlet: 3" V-Band Turbine Inlet: 3" V-Band/T4 open/ T4 divided Water Ports: -6AN Oil Feed Fitting(-4AN 1.65mm (0.065") Orifice) included Oil Drain: -12AN(O-Ring sealed Flange Kit Included)