

Link do produktu: <https://bizongarage.pl/zbiornik-paliwa-surge-tank-nuke-performance-25-litrow-homologacja-fia-p-4524.html>



Zbiornik paliwa + Surge Tank Nuke Performance 25 litrów homologacja FIA

| | |
|------------------|----------------------|
| Cena brutto | 11 399,00 zł |
| Cena netto | 9 267,48 zł |
| Dostępność | Na zamówienie |
| Numer katalogowy | 331553389 |
| Kod producenta | NP-150-09-025 |

Opis produktu

LightCell Fuel Cell with Nuke Performance CFC Unit Specifications: For more information about specifications, view the product manual. Part numbers shown as: HP=High Profile CFC Unit / B=Brushless CFC Unit 25 liter fuel cell Part # 1500-09-501 (HP:150-09-025 / B:150-09-125) Length 395mm (15.55") +25mm (1") flange on all sides Depth 335mm (13.19") +25mm (1") flange on all sides Height 210mm (8.27") Weight 5420g (11.95lb) without CFC unit Fuel capacity 25-liter (7 gallons) For motorsports use YES Homologation YES, 5 year homologation Fuel level sender 150-FLS-08 : 203 mm (8") EAN HP:7340209506556 / B:7340209506563 35 liter fuel cell Part # 1500-09-502 (HP:150-09-035 / B:150-09-135) Length 526mm (20.71") +25mm (1") flange on all sides Depth 335mm (13.19") +25mm (1") flange on all sides Height 210mm (8.27") Weight 6750g (14.88lb) without CFC unit Fuel capacity 35-liter (9 gallons) For motorsports use YES Homologation YES Fuel level sender 150-FLS-08 : 203 mm (8") EAN HP:7340209506570 / B:7340209506587 45 liter fuel cell Part # 1500-09-503 (HP:150-09-045 / B:150-09-145) Length 526mm (24.80") +25mm (1") flange on all sides Depth 335mm (22.05") +25mm (1") flange on all sides Height 270mm (8.86") Weight 7450g (16.42lb) without CFC unit Fuel capacity 45-liter (12 gallons) For motorsports use YES Homologation YES Fuel level sender 150-FLS-10 : 254mm (10") EAN HP:7340209506594 / B:7340209506600 55 liter fuel cell Part # 1500-09-504 (HP:150-09-055 / B:150-09-155) Length 526mm (24.80") +25mm (1") flange on all sides Depth 405mm (15.94") +25mm (1") flange on all sides Height 270mm (8.86") Weight 8320g (18.34lb) without CFC unit Fuel capacity 55-liter (15 gallons) For motorsports use YES Homologation YES Fuel level sender 150-FLS-10 : 254mm (10") EAN HP:7340209501414 / B:7340209501421 Nuke Performance CFC Unit - High Profile / Brushless specifications: Included CFC Unit Part # HP:150-05-203 / B:150-05-204 Minimum mounting depth 197mm (7.75") Mounting bolt pattern 6x10" 24-bolt pattern High-pressure fuel pump connector 6mm x 3 (max 125 ampere / each) * Pickup fuel pump connector 6mm x 2 (max 125 ampere / each) Length 295mm (13.74") Width 194mm (9.88") Weight HP:2254g (4.96lb) / B:2290g (5.05lb) Fits number of lift fuel pumps 1 x in-tank fuel pump Fits number of high-pressure pumps 1 or 2 x in-tank fuel pumps ** High-pressure fuel pump compatibility Outer diameter: 39 mm (1.53") Outer diameter: 42 mm (1.65") Outer diameter: 46 mm (1.81") Fuel compatibility Gasoline, Methanol, Ethanol, E85 Internal surge tank volume Approximately 2.0 liter (0.53 gallons) Outlet port, thread AN-10 ORB, view range Return port, thread AN-8 ORB, view range Vent valve, thread AN-8 (3/4 UNF), view range Vent valve fitting included AN-8 (3/4 UNF) to AN-6 Male For motorsports use YES * Depending on the selected CFC Unit version. The brushless version uses a 6-pin bulkhead connector for the high-pressure fuel pumps. ** Suits most common in-tank fuel pumps with a 39, 42, and 46mm outer diameter. Known compatibility with AEM 320L E85, Deatschwerks DW200, 300, 400, 420, 440, 810, and Ti Automotive (Walbro) GST400, 450, 500, 520, 525. LightCell Fuel Cell with Nuke Performance CFC Unit includes: 1 x LightCell fuel cell 25 liter / 35 liter / 45 liter / 55 liter 1 x Nuke Performance CFC Unit * 2 x 1/4" BSPP to Male barb 8mm hose fittings 2 x 39mm inserts for high-pressure fuel pump bracket 2 x Viton gasket for 24 bolt pattern fuel cells (safe for alcoholic fuels) 1 x Low profile filler cap (remote fill neck available as accessory) 1 x Dual billet fuel pump bracket and adjustable pickup pump mount 1 x AN-8 (3/4 UNF) to AN-6 Male vent safety valve 1 x FLS spacer, used for fuel level senders with a not symmetrical bolt pattern 24 x 1/4-28 UNF x 1 bolts with nylon washers * Delivered CFC Unit version depends on which one is selected when ordered, specifications are listed below. No fuel pumps are included with the LightCell fuel cell : The LightCell fuel cell from Nuke Performance is available with or without a CFC Unit. When ordering a CFC Unit, you must choose a model for traditional in-tank or brushless fuel pumps. Regardless of the version, no fuel pumps are included and must be purchased separately. Manufactured to order, delivery time approx 3-6 weeks. All LightCell fuel cells are custom-manufactured to order, ensuring you receive the latest FIA-homologated design and never an outdated or stored bladder. This guarantees maximum performance, safety, and compliance. We also keep select sizes in stock for faster delivery—contact us to check availability. If your preferred size is unavailable, the estimated production and delivery time is 4-6 weeks, ensuring a fresh, high-quality product tailored to your needs.