

Link do produktu: <https://bizongarage.pl/zbiornik-paliwa-surge-tank-uke-performance-45-litrow-homologacja-fia-p-4526.html>

BRAK
ZDJĘCIA



Zbiornik paliwa + Surge Tank Nuke Performance 45 litrów homologacja FIA

Cena brutto	11 569,99 zł
Cena netto	9 406,50 zł
Cena poprzednia	14 279,07 zł
Dostępność	Na zamówienie
Numer katalogowy	331553391
Kod producenta	NP-150-09-045

Opis produktu

LightCell Fuel Cell with Nuke Performance CFC Unit Specifications:

For more information about specifications, view the product manual.

Part numbers shown as: HP=High Profile CFC Unit / B=Brushless CFC Unit

25 liter fuel cell Part #	1500-09-501 (HP:150-09-025 / B:150-09-125)
Length	395mm (15.55") +25mm (1") flange on all sides
Depth	335mm (13.19") +25mm (1") flange on all sides
Height	210mm (8.27")
Weight	5420g (11.95lb) without CFC unit
Fuel capacity	25-liter (7 gallons)
For motorsports use	YES
Homologation	YES, 5 year homologation
Fuel level sender	150-FLS-08 : 203 mm (8")
EAN	HP:7340209506556 / B:7340209506563
35 liter fuel cell Part #	1500-09-502 (HP:150-09-035 / B:150-09-135)
Length	526mm (20.71") +25mm (1") flange on all sides
Depth	335mm (13.19") +25mm (1") flange on all sides
Height	210mm (8.27")
Weight	6750g (14.88lb) without CFC unit
Fuel capacity	35-liter (9 gallons)
For motorsports use	YES
Homologation	YES
Fuel level sender	150-FLS-08 : 203 mm (8")
EAN	HP:7340209506570 / B:7340209506587
45 liter fuel cell Part #	1500-09-503 (HP:150-09-045 / B:150-09-145)
Length	526mm (24.80") +25mm (1") flange on all sides
Depth	335mm (22.05") +25mm (1") flange on all sides
Height	270mm (8.86")
Weight	7450g (16.42lb) without CFC unit
Fuel capacity	45-liter (12 gallons)
For motorsports use	YES

Homologation	YES
Fuel level sender	150-FLS-10 : 254mm (10")
EAN	HP:7340209506594 / B:7340209506600
55 liter fuel cell Part #	1500-09-504 (HP:150-09-055 / B:150-09-155)
Length	526mm (24.80") +25mm (1") flange on all sides
Depth	405mm (15.94") +25mm (1") flange on all sides
Height	270mm (8.86")
Weight	8320g (18.34lb) without CFC unit
Fuel capacity	55-liter (15 gallons)
For motorsports use	YES
Homologation	YES
Fuel level sender	150-FLS-10 : 254mm (10")
EAN	HP:7340209501414 / B:7340209501421

Nuke Performance CFC Unit - High Profile / Brushless specifications:

Included CFC Unit Part #	HP:150-05-203 / B:150-05-204
Minimum mounting depth	197mm (7.75")
Mounting bolt pattern	6x10" 24-bolt pattern
High-pressure fuel pump connector	6mm x 3 (max 125 ampere / each) *
Pickup fuel pump connector	6mm x 2 (max 125 ampere / each)
Length	295mm (13.74")
Width	194mm (9.88")
Weight	HP:2254g (4.96lb) / B:2290g (5.05lb)
Fits number of lift fuel pumps	1 x in-tank fuel pump
Fits number of high-pressure pumps	1 or 2 x in-tank fuel pumps **
High-pressure fuel pump compatibility	Outer diameter: 39 mm (1.53") Outer diameter: 42 mm (1.65") Outer diameter: 46 mm (1.81")
Fuel compatibility	Gasoline, Methanol, Ethanol, E85
Internal surge tank volume	Approximately 2.0 liter (0.53 gallons)
Outlet port, thread	AN-10 ORB, view range
Return port, thread	AN-8 ORB, view range
Vent valve, thread	AN-8 (3/4 UNF), view range
Vent valve fitting included	AN-8 (3/4 UNF) to AN-6 Male
For motorsports use	YES

* Depending on the selected CFC Unit version. The brushless version uses a 6-pin bulkhead connector for the high-pressure fuel pumps.

** Suits most common in-tank fuel pumps with a 39, 42, and 46mm outer diameter. Known compatibility with AEM 320L E85, Deatschwerks DW200, 300, 400, 420, 440, 810, and Ti Automotive (Walbro) GST400, 450, 500, 520, 525.

LightCell Fuel Cell with Nuke Performance CFC Unit includes:

1 x LightCell fuel cell 25 liter / 35 liter / 45 liter / 55 liter
 1 x Nuke Performance CFC Unit *
 2 x 1/4" BSPP to Male barb 8mm hose fittings
 2 x 39mm inserts for high-pressure fuel pump bracket
 2 x Viton gasket for 24 bolt pattern fuel cells (safe for alcoholic fuels)
 1 x Low profile filler cap (remote fill neck available as accessory)
 1 x Dual billet fuel pump bracket and adjustable pickup pump mount
 1 x AN-8 (3/4 UNF) to AN-6 Male vent safety valve
 1 x FLS spacer, used for fuel level senders with a not symmetrical bolt pattern
 24 x 1/4-28 UNF x 1 bolts with nylon washers

* Delivered CFC Unit version depends on which one is selected when ordered, specifications are listed below.

No fuel pumps are included with the LightCell fuel cell :

The LightCell fuel cell from Nuke Performance is available with or without a CFC Unit. When ordering a CFC Unit, you must choose a model for traditional in-tank or brushless fuel pumps. Regardless of the version, no fuel pumps are included and must be purchased separately.

Manufactured to order, delivery time approx 3-6 weeks.

All LightCell fuel cells are custom-manufactured to order, ensuring you receive the latest FIA-homologated design and never an outdated or stored bladder. This guarantees maximum performance, safety, and compliance. We also keep select sizes in stock for faster delivery—contact us to check availability. If your preferred size is unavailable, the estimated production and

delivery time is 4-6 weeks, ensuring a fresh, high-quality product tailored to your needs.